

Industrial connectivity solutions



FLYING LEVER TERMINAL BLOCK

EASY, FAST, SAFE

THE EVOLUTION OF THE SPECIES

IN ONE CLICK!





Cabur presents the UC series, a new line of flying lever terminal blocks. The line includes easy of use 2.5 mm² and 4 mm² terminals, with two, three and five poles.


The exceptional versatility can be applied in various application such as building automation, small/medium industrial automation, shipbuilding and domestic installation.



Advantages:


- Very fast connection thanks to the lever, no additional tools required
- Direct push-in type connection of rigid cables or cables equipped with ferrules
- Connection and removal of flexible cables with the lever
- Transparent body for quick inspection of correct wiring
- The clamp avoids the risk of breaking of the cable caused by the direct tightening of the screw
- The pole connection avoids the cables twisting and the risk of overheating



TECHNICAL DATA

- Push-in technology
- Quick installation without using tools
- Safe connection of different wire section
- Compatible with both rigid and flexible cables
- Poor contacts risks reduced



Code		UC02M	UC03M	UC05M
Poles number		2	3	5
Dimensions (WxDxH)		11x17x9 mm	15.5x17x9 mm	24.5x17x9 mm
Cross section	Rigid cable	0.2 - 2.5 mm ²		
	Flexible cable	0.34 - 2.5 mm ²		
Insulation stripping length		11 mm		
Nominal voltage		450 V		
Nominal current		24 A		
Max. operating temperature		85° C		
Plastic material		Polycarbonate		
Flammability index		94-V2		
Box units		100	100	50
Approvals		 		



Code		UC02	UC03	UC05
Poles number		2	3	5
Dimensions (WxDxH)		13x21x11 mm	19x21x11 mm	30x21x11 mm
Cross section	Rigid cable	0.2 - 4.0 mm ²		
	Flexible cable	0.34 - 4.0 mm ²		
Insulation stripping length		11 mm		
Nominal voltage		450 V		
Nominal current		32 A		
Max. operating temperature		85° C		
Plastic material		Polycarbonate		
Flammability index		94-V2		
Box units		100	50	25
Approvals		 		



AUTOMATION
AND CONTROL
SOLUTIONS



INDUSTRIAL
CONNECTIVITY
SOLUTIONS



SOLUTIONS
FOR RENEWABLE
ENERGY



INDUSTRIAL
MARKING
SOLUTIONS



D042G21A

Cabur Srl

Headquarters (Italia)

17041 - Altare (SV)

Località Isola Grande, 45

T. +39 019 58999.1

F. +39 019 58999233

www.cabur.it

info@cabur.it

Cabur Romania Srl

Romanian Branch

Strada Calea Plevnei nr. 139

Corp B camera 25,26 sector 6

Bucaresti

T. +40 (21)31.17.140

F. +40 (21)31.17.140

www.cabur.eu

gabriel.buzaianu@cabur.eu